

# 4" CAST IRON CLOSET FLANGE

890 Series

Item Number  
Submitted:

890-i42

## **SPECIFICATION:**

Installed closet flanges shall be Sioux Chief 890 Series cast iron closet flange. Closet flange shall have three screw holes for securing to floor, and two closet bolt slots. Internal neoprene compression gasket shall create seal when lock-ring is tightened via three stainless steel bolts. Flange shall employ a neoprene test cap which shall hold a 30 PSI air test. Flange shall be UPC listed.

## **MATERIALS:**

FLANGE TOP: Cast iron  
COMPRESSION LOCK-RING: Cast iron  
GASKET/TEST CAP: Neoprene  
LOCK-RING BOLTS: Stainless steel

## **CONNECTION TYPE:**

Push-fit over 4" cast iron, as three bolts are tightened, compression gasket creates seal

## **HOLE/SLOT CONFIGURATION:**

Three screw holes for securing to floor.  
Two slots for fastening closet bolts to ring

## **INSTALLATION:**

Push flange over 4" cast iron DWV pipe. Fasten flange to floor using three screw holes. Tighten compression gasket with three hex-head bolts. Test cap will hold up to 30 PSI air test. After air test, cut out test cap with utility knife.

## **DIMENSIONS:**

Overall Diameter	A: 7"
Screw Centers	B: 5"
Test Cap Diameter	C: 4 <sup>3</sup> / <sub>8</sub> "
Connection	D: Over 4" cast iron
Overall Height	E: 2"



890-i42  
shown

