

DUAL HANDLE WATER SUPPLY STOPS

/// 133-G SERIES DUAL HANDLE, 134-G SERIES DUAL HANDLE

SPECIFICATION

Tomahawk 133-G or 134-G series Dual Handle Water Supply Stops shall be used as a means of controlling pressure water connections to plumbing fixtures for the purpose of being able to turn off flow for repairs or emergency situations.

INSTALLATION

Attach to pressure piping as prescribed by inlet connection on stop valve. Connect supply hose of desired configuration to outlet of supply.

MATERIALS

Valve body: no lead brass
Sleeve: brass
Nut: brass
Finish: chrome or rough brass

FEATURES

- available in straight and angle configurations
- certified to NSF/ANSI 61 Section 9-G
- IAPMO Listed
- no lead brass

PACKAGING

Individually boxed

PRESSURE & TEMPERATURE

Maximum pressure: 125psi / 8.6 bar
Maximum temperature: 160°F / 71.1°C

DIMENSIONS

*Tomahawk specifications in US customary units are approximate and are provided for reference only.

	3-G2C1C1CDHR1	4-G2C1C0CDHR1	4-G2C1C1CDH	4-G2C1C1CDHR1
A: outlet center to center	1.375"	1.375"	1.375"	1.375"
B: height	2.5"	2.5"	2.5"	2.5"
C: length	4.375"	4.375"	4.375"	4.375"



ITEM # SUBMITTED	_____
JOB NAME	_____
LOCATION	_____
ENGINEER	_____
CONTRACTOR	_____
PO#	_____ TAG _____



133-G2C1C1CDHR104



134-G2C1C1CDHR104



*The wetted surface of this product contacted by consumable water contains less than 0.25% of lead by weight.



Create Item Number

13A-G2C1CBDHC04

e.g. **133-G2C1C1CDHR104:** straight multi-turn stop, 5/8" O.D. X 3/8" O.D. X 3/8" O.D. compression, dual handle multi-turn, 1/bx

ITEM A	CONNECTION B	FINISH C
3 = straight multi-turn	0C = 1/4" compression	_ = chrome
4 = angle multi-turn	1C = 3/8" compression	R1 = rough brass



*Not all combinations available. Contact your local rep to confirm availability.