

# FLEXIBLE SUPPLY TUBES – TOILET

## /// 283-T SERIES, 285-T SERIES

### SPECIFICATION

Tomahawk 283-T and 285-T Flexible Supply Tubes shall be used for connecting water supply to toilet and shall meet or exceed ASME A112.18.6.

### INSTALLATION

Connect to supply valve making sure nylon or brass ferrule is positioned on tube.

### MATERIALS

**Tube:** PEX with molded head or rough brass (copper) with or without a rubber nose cone

**Finish:** chrome-plated or PEX

**Ferrule:** nylon or brass

### FEATURES

- available lengths: 12", 16" and 20"

### CERTIFICATIONS

ASME A112.18.6

NSF-PW-G

ASTM F876

ITEM # SUBMITTED	_____
JOB NAME	_____
LOCATION	_____
ENGINEER	_____
CONTRACTOR	_____
PO#	_____ TAG _____




283-T24112C00




285-T2412000




283-T25112C00



Rubber Nose Cone



PEX Nose Cone



With Flat Washer

\*The wetted surface of this product contacted by consumable water contains less than 0.25% of lead by weight.

## Create Item Number

### 28A-TB1CCD

e.g. **283-T24112C00**: rough brass (copper), 3/8" O.D. tube x 7/8" w/ rubber nose cone, 12", 100/bx

#### CATEGORY **A**

**283** = rough brass (copper)

**285** = PEX

#### INLET x OUTLET **B**

**24** = 3/8" O.D. tube X 7/8" w/ rubber nose cone

**25** = 3/8" O.D. tube X 7/8" with flat washer

#### LENGTH **C**

**12** = 12"

**16** = 16"

**20** = 20"

#### PACKAGE **D**

**00** = packed 100 per box

**50** = packed 50 per box



\*Not all combinations available. Contact your local rep to confirm availability.