## **HEATER HOSE**

## /// EPDM RUBBER

### **SPECIFICATION**

Rubber heater hose is manufactured with lightweight EPDM rubber reinforced with multiple textile plies. It has excellent resistance to heat, ozone, and weather conditions, with limited oil resistance. It is designed for use with automotive coolant under standard operating temperatures and pressures. This tubing can also be used as a dishwasher or washing machine discharge hose.

#### **ATTRIBUTES**

- Smooth, dense bore maximizes flow and reduces sediment buildup
- This black EDPM tubing is UV and ozone resistant

#### **MATERIALS**

Heater hose is manufactured with lightweight EPDM rubber reinforced with multiple textile piles.

#### **APPLICATIONS**

- Designed for use with automotive coolant under standard operating temperatures and pressures
- Can also be used on dishwasher and washing machine discharge hose

#### RESISTANCE

Heat, ozone, and weather conditions, with limited oil resistance. (See list on website for listing of chemicals)

Operating temperature range: -40°F (-40°C) to 212°F (100°C)

Material: EPDM rubber

Color: Black

Hardness: Durometer Shore A 75+/-3

Bend radius: 6" - 9"

#### **PACKAGING**

Coils, reels

\*Custom lengths available in large quantity only. Contact your local rep to confirm availability.

### PRESSURE RANGE

I.D. Inch	O.D. Inch	WALL INCH	WORKING PRESSURE (PSI @ 70°F)
1/2	3/4	1/8	105
5/8	7/8	1/8	80
3/4	1	1/8	200
1	1-11/32	11/64	_





WARNING: Not intended for use with potable water.

## Create Item Number

# 900-12 <u>ABNCD</u>

e.g. 900-12206N00101: Heater Hose 1/2" ID X 3/4" OD (1/8" Wall), Black, 10ft Coil

ID SIZE A	WALL <u>B</u>	LENGTH <u>C</u>	PACKAGE <u>D</u>
<b>20</b> = 1/2"	<b>6</b> = 1/8"	<b>0010</b> = 10ft	1 = Coils
<b>25</b> = 5/8"	<b>7</b> = 11/64"	<b>0050</b> = 50ft	<b>5</b> = Reels
<b>30</b> = 3/4"		<b>0075</b> = 75ft	
<b>40</b> = 1"		<b>0100</b> = 100ft	



\*Not all size, wall thickness and length combinations available. Contact your local rep to confirm availability.