DWV PIPE HANGER

>> 510 SERIES

SPECIFICATION

Sioux Chief's 510 series DWV Pipe hanger shall be used where necessary to secure Schedule 40 DWV piping in accordance with all local and national codes. Hanger shall be of galvanized steel material to resist rust. Vinyl-coated option shall be available for use on plastic pipe to isolate and prevent direct contact with metal hanger. Hanger shall have a 12" stem length to the top of the pipe loop. Hanger stem shall have alternating hole sizes.

INSTALLATION

Secure hanger stem to joist with nail or screw. Wrap loop around pipe. Tighten locking screw once pipe is installed to secure pipe in place. Be sure to follow code requirements on proper pipe slope.

MATERIALS

Hanger: galvanized steel

Vinyl: Plastisol

Screw: #12-11 x 1-3/8" combo self-tapping with bunt point

MAXIMUM LOAD RATING

150 lbs.


DIMENSIONS

Ga	uge:
	DWA

	DWV Pipe Size	1-1/2"	2"	3"	4"		
	Galvanized	18	18	16	16		
	Vinyl-Dipped	18	18	16	16		
Width:							
	DWV Pipe Size	1-1/2"	2"	3"	4"		
	Galvanized	3/4"	3/4"	3/4"	3/4"		
	Vinyl-Dipped	1"	1"	1"	1"		
A:	stem length	12"	12"	12"	12"		
B:	large hole	0.275"	0.275"	0.275"	0.275"		
C:	small hole	0.188"	0.188"	0.188"	0.188"		
D:	centerline	0.86"	0.86"	0.86"	0.86"		

ITEM # SUBMITTED	
JOB NAME	
LOCATION	
ENGINEER	
CONTRACTOR	
PO#	TAG





MADE IN USA

Create Item Number

510-AB

e.g. 510-8VPK: 3" vinyl-coated DWV pipe hanger

DWV PIPE SIZE A

6 = 1½"

7 = 2"

8 = 3"

9 = 4"

FINISH B

PK = galvanized steel

VPK = vinyl-coated galvanized