# **TUBE INSULATOR FOR CTS PIPING**

# >> 558 SERIES

#### **SPECIFICATION**

Sioux Chief 558 series Tube Insulator to be used where necessary to insulate CTS piping in residential or commercial applications. Insert in to wood or metal studs and mount to surface using nail or screw in both of the clamp's provided holes. Fits in to 1%" hole for wood studs or  $1^{1/32}$ " hole for metal studs.

### MATERIALS

Low density polyethylene

## WORKING TEMPERATURE

Maximum temperature:  $180^{\circ}$ F continuous impact resistant to  $0^{\circ}$ F (- $18^{\circ}$ C)

ITEM # SUBMITTED
JOB NAME
LOCATION
ENGINEER
CONTRACTOR
PO# TAG





**Create Item Number** 

**558-A** e.g. 558-3: Tube Insulator for <sup>3</sup>/<sub>4</sub>" CTS piping **TUBE SIZE A 2** = <sup>1</sup>/<sub>2</sub>" CTS **2PK2** = <sup>1</sup>/<sub>2</sub>" CTS, 5/bag **3** = <sup>3</sup>/<sub>4</sub>" CTS **3PK2** = <sup>3</sup>/<sub>4</sub>" CTS, 5/bag **4** = 1" CTS

