ADJUSTABLE FLASHING DRAIN

>> 832 SERIES

FinishLine[™]

SPECIFICATION

Sioux Chief 832 series FinishLine™ adjustable floor drain shall be used where necessary in drainage systems. Floor drain shall allow adjustment before and AFTER the concrete pour. Strainer shall be heel-resistant and meet applicable load requirements for intended use. Trap primer port shall be threaded 1/2" FIP for optional connection.

Designed in accordance with ASME A112.6.3-2001

MATERIALS

Ring/strainer: Nickel-bronze, 304 Stainless steel

Head adapter/Coring sleeve: gray ABS Coring plug: high-impact polymer

Base adapter: ABS, PVC

STRAINER LOAD RATING

Nickel-Bronze: 1,650 lbs. (light duty) **Stainless Steel:** 2,000 lbs. (light duty)

STRAINER FREE AREA

Round: 8.5 in² **Square:** 12.75 in²

DIMENSIONS

2" x 3", 3" x 4" Sch. 40 Hub A: Connection size

B: Ring/strainer diameter

Round | Square 5-1/2" | 5-7/8"

C: Base adapter height 3-1/2"

D: Pre-pour adjustable height 4-5/8"- 5-1/2"


E: Post-pour adjustable height

Round | Square 0" - 1" | 5/16" - 1"

F: Trap primer port Knockout - 1/2" FIP thread







Create Item Number

832-ABCD

e.g. 832-25PNRV: FinishLine 2" PVC Sch. 40 hub adjustable floor drain with nickel-bronze ring and strainer

CONNECTION SIZE A

25 = 2" Sch. 40 Hub 35 = 3" Sch. 40 Hub

CONNECTION TYPE B

A = ABS base adapter P = PVC base adapter RING/STRAINER TYPE C

NR = Round Nickel-bronze SR = Round Stainless steel **NQ** = Square Nickel-bronze

SQ = Square Stainless steel

OPTIONS D

V = Vandal-resistant strainer screws

B = Complies with BABAA¹

 $\mathbf{E} = 1-1/4$ " Extended strainer rim¹

Accessories - Available Separately:

832-3HHD: Std. Top hub drain finish fixture 832-EPS3: Extended ABS coring sleeve & plug 832-EX3: Iron extension adapter for Std. top2

832-P: Coring Plug wrench

832-S3: Leveling shim kit for Std. top 832-W: Flexible locating bristles kit 835-2: TrapShield™ for 2" drain outlet 835-3: TrapShield[™] for 3" drain outlet

863-FA: Round aluminum condensate funnel 863-FN: Round nik-brz condensate funnel

1 Available for round nickel-bronze strainers only | 2 Extends head 2" (min) to 4" (max) above Coring Sleeve



05-23